

# TECHNICAL DATA

## ACCESS 100 BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |            |
|-------------|------------|
| Part number | AS3634     |
| Model       | ACCESS 100 |
| Type        | 36V/205A   |

### MAINS DATA (50/60HZ)

|                                |              |
|--------------------------------|--------------|
| Output Voltage [V]             | 36           |
| Output Current [A]             | 205          |
| Number of phases               | 3            |
| Rated Voltage range [V]        | 440-440      |
| Current at nominal voltage [A] | 13,5         |
| Recommended supply fuse [A]    | 16           |
| Supply cable area              | 4x2,5        |
| Supply cable length [m]        | 3            |
| Typical Supply Connector       | Not included |
| Output cable cross-section     | 2x70         |

### BATTERY CONNECTION

|                                  |              |
|----------------------------------|--------------|
| Output cable cross-section       | 2x70         |
| Output cable terminals (in unit) | M8           |
| Output cable length [m]          | 3            |
| Typical Output connector         | User defined |
| Output Voltage [V]               | 36           |

### ELECTRIC DATA

|                                 |       |
|---------------------------------|-------|
| Standby Power Consumption [W]   | < 10  |
| Power Consumption [W]           | 9763  |
| Apparent Power Consumption [VA] | 10277 |

|  |            |
|--|------------|
| Power Factor                                   | 0,95       |
| Inrush current, do not tripp fuse of class [A] | Negligible |
| Output Ripple                                  | <1         |
| Efficiency (at rated power and no cables) [%]  | 92         |

## PROPERTIES

|  |                        |
|--|------------------------|
| Ingress protection                                       | IP20                   |
| Ambient temperature range (at full output power) [deg C] | -5 to +40              |
| Ambient max temp (with reduced output power) [deg C]     | 50                     |
| Cooling  | Fan                    |
| Short Circuit Protection                                 | 1                      |
| Wrong Polarity Protection                                | Fuse                   |
| Cabinet Type   | A18                    |
| Certifications   | CE                     |
| HMI  | LED / Display          |
| HMI Language   | SV / EN / ES / PT / DE |
| Reporting  | Yes                    |
| Radio Communication                                      | Yes                    |
| Charging Curve Set                                       | Multiple               |
| I/O-cards  | Optional               |
| CE   | No                     |
| UL   | No                     |

## CHARGING TIMES

|                    |      |
|--------------------|------|
| 6 Hours cap.ah/5h  | 1178 |
| 8 Hours cap.ah/5h  | 1707 |
| 10 Hours cap.ah/5h | 2277 |
| 12 Hours cap.ah/5h | 2732 |

## CHARGER DIMENSIONS

|                              |     |
|------------------------------|-----|
| Weight excl. cables [kg]     |     |
| Weight incl. cables [kg]     |     |
| Outer Dimensions Height [mm] | 529 |

|                             |     |
|-----------------------------|-----|
| Outer Dimensions Width [mm] | 256 |
| Outer Dimensions Depth [mm] | 243 |
| Min Spacing Required        | 300 |

## SHIPPING DIMENSIONS

|                      |     |
|----------------------|-----|
| Shipping Weight [kg] | 25  |
| Box Height [mm]      | 440 |
| Box Width [mm]       | 370 |
| Box Depth [mm]       | 650 |

## CHARGING

|                     |                        |
|---------------------|------------------------|
| Charging Ionic      | LK10-18 Ionic mixture  |
| Charging Standard   | LK10-06 Standard Curve |
| Charging Gel        | LK20-09                |
| Charging Li-Ion     | 0                      |
| Charging AGM        | LK20-09                |
| Moisture Resistance | No                     |
| Dusty Environment   | No                     |
| Outdoor use         | No                     |
| Cold store          | No                     |
| Tropical            | No                     |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.